

# MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE



## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

<b>Product type:</b>	Solder wire containing Lead/Tin
<b>Intended use:</b>	Soldering
<b>Trade Name:</b>	BOSS Leaded Solder Wire
<b>Supplier of product:</b>	The BSS Group plc
<b>Registered Office:</b>	Fleet House, Lee Circle, Leicester, LE1 3QQ
<b>Telephone/Fax Numbers:</b>	0116 262 3232 / 0116 253 1343
<b>E-mail Address</b>	reception@bssgroup.com
<b>Web site Address</b>	www.bss-group.co.uk

## 2. HAZARD IDENTIFICATION

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments	
<b>Classification:</b>	Not classified
<b>Skin Contact:</b>	Non-irritant to skin
<b>Toxicity Data:</b>	Lead: Warning. Contains lead Over-exposure signs/symptoms:- blood formation impairment, central nervous system depression May cause harm to the unborn child Repeated or prolonged exposure to the substance can produce reproductive system damage
<b>Additional Warning Phrases:</b>	Safety data sheet available for professional user on request
See section 11 for more detailed information on health effects and symptoms	

## 3. COMPOSITION/INFORMATION ON INGREDIENTS.

<b>Substance/Preparation:</b>	Preparation			
<b>Ingredient Name</b>	<b>CAS No</b>	<b>%</b>	<b>EC No</b>	<b>Classification</b>
<b>Europe</b>				
Lead	7439-92-1	60-80	231-100-4	Repr. Cat.1; R1 Repr. Cat 3; R62 Xn; R20/22 R33 N; R60/53
Tin	7440-31-5	20-30	231-141-8	Not classified
Antimony	7440-36-0	1-5	231-146-5	Xn; R20/22 N; R51/53
See section 16 for the full text of the R-phrases declared above				
* Occupational Exposure Limit(s), if available, are listed in Section 8				
* The classification listed, indicate the potential hazards of the ingredients				

# MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

## 4. FIRST AID MEASURES

<b>Skin Contact:</b>	Flush contaminated skin with plenty of water. Cuts should be treated promptly and covered
<b>Eye Contact:</b>	Get medical attention if any damage to the eye is caused by the metal
<b>Protection of First-Aiders</b>	No action shall be taken involving any personal risk or without suitable training
<b>Notes to Physician:</b>	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
<b>See section 11 for more detailed information on health effects and symptoms</b>	

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media</b>	
<b>Suitable:</b>	Use an extinguishing agent suitable for surrounding fire
<b>Not Suitable:</b>	None known
<b>Special Exposure Hazards:</b>	No specific fire or explosion hazard Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
<b>Hazardous combustion:</b>	Decomposition products may include the following materials: Metal oxide/Oxides
<b>Special Protective Equipment for Fire-Fighting:</b>	No special protection is required

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	No action shall be taken involving any personal risk or without suitable training Evacuate surrounding areas Keep unnecessary and unprotected personnel from entering
<b>Environmental Precautions:</b>	No specific hazard
<b>Large Spill:</b>	Restack safely. Take care with items that are sharp or heavy
<b>Small Spill:</b>	Restack safely. Take care with items that are sharp or heavy

## 7. HANDLING AND STORAGE:

<b>Handling:</b>	Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Take care with items that are sharp or heavy
<b>Storage:</b>	Store in accordance with local regulations
<b>Packaging Material</b>	
<b>Recommended:</b>	Use original container

# MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limit Values		
<b>Europe:</b>	Lead	<b>EU OEL (Europe, 5/2006). Notes: Binding</b> 8 hours: 0.15 mg/m <sup>3</sup> 8 hour(s).
	Tin	<b>ACGIH TLV (United States, 1/2006).</b>
	Antimony	<b>ACGIH TLV (United States, 1/2006). Notes: as Sb</b>
<b>Sweden:</b>	Lead	<b>AFS (Sweden, 6/2005).</b> TWA: 0.05 mg/m <sup>3</sup> 8 hour(s). Form: respirable dust
	Antimony	TWA: 0.1 mg/m <sup>3</sup> 8 hour(s). Form: total dust <b>AFS (Sweden, 6/2005).</b> TWA: 0.5 mg/m <sup>3</sup> 8 hour(s). Form: total dust
<b>Denmark:</b>	Lead	<b>Arbejdstilsynet (Denmark, 4/2005). Notes: Calculated as Pb</b> TWA: 0.05 mg/m <sup>3</sup> , (Calculated as Pb) 8 hour(s). Form: Powder, dust and fumes
	Antimony	<b>Arbejdstilsynet (Denmark, 4/2005). Notes: Calculated as Sb</b> TWA: 0.5 mg/m <sup>3</sup> , (Calculated as Sb) 8 hour(s). Form: Powder
<b>Norway:</b>	Lead	<b>Arbejdstilsynet (Norway, 10/2003). Notes: Calculated as Pb</b> TWA: 0.05 mg/m <sup>3</sup> , (Calculated as Pb) 8 hour(s). Form: Dust and fumes
	Antimony	<b>Arbejdstilsynet (Norway, 10/2003).</b> TWA: 0.5 mg/m <sup>3</sup> 8 hour(s).
<b>France:</b>	Lead	<b>INRS (France, 6/2006). Notes: Regulatory binding exposure limits</b> TWA: 0.1 mg/m <sup>3</sup> 8 hour(s).
	Antimony	<b>INRS (France, 6/2006). Notes: indicative exposure limits</b> TWA: 0.5 mg/m <sup>3</sup> 8 hour(s).
<b>Netherlands:</b>	Lead	<b>Nationale MAC-lijst (Netherlands, 7/2006). Notes: Legal indicates a statutory value, Administrative indicates an administrative value that is not legally binding (see background).</b> OEL, 8-h TWA: 0.15 mg/m <sup>3</sup> 8 hour(s). Form: respirable dust and fume
	Antimony	<b>Nationale MAC-lijst (Netherlands, 7/2006).</b> <b>Notes: Administrative</b> OEL, 8-h TWA: 0.5 mg/m <sup>3</sup> 8 hour(s).
<b>Germany:</b>	Lead	<b>EU OEL (Europe, 5/2006). Notes: Binding</b> 8 hours: 0.15 mg/m <sup>3</sup> 8 hour(s).
<b>Finland:</b>	Tin	<b>Työterveyslaitos (Finland, 2002).</b> TWA: 2 mg/m <sup>3</sup> 8 hour(s). <b>Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 4/2005).</b> <b>Notes: Calculated as Sn</b> TWA: 2 mg/m <sup>3</sup> , (Calculated as Sn) 8 hour(s).
	Antimony	<b>Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 4/2005).</b> <b>Notes: Calculated as Sb</b> TWA: 0.5 mg/m <sup>3</sup> , (Calculated as Sb) 8 hour(s).

**MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE**

<p><b>United Kingdom (UK)</b></p>	<p>Lead</p> <p>Tin</p> <p>Antimony</p>	<p><b>EH40-OES (United Kingdom (UK), 2002).</b> TWA: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>EH40-WEL (United Kingdom (UK), 9/2006).</b> WEL 8 hrs limit: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>EH40-OES (United Kingdom (UK), 2002).</b> TWA: 2 mg/m<sup>3</sup> 8 hour(s). STEL: 4 mg/m<sup>3</sup> 15 minute(s).</p> <p><b>EH40-WEL (United Kingdom (UK), 9/2006). Notes: As Sb</b> WEL 8 hrs limit: 0.5 mg/m<sup>3</sup>, (As Sb) 8 hour(s). TWA: 0.5 mg/m<sup>3</sup>, (Calculated as Sb) 8 hour(s).</p>
<p><b>Austria</b></p>	<p>Lead</p> <p>Tin</p> <p>Antimony</p>	<p><b>GKV_MAK (Austria, 6/2006).</b> STEL: 0.4 mg/m<sup>3</sup>, 4 times per shift, 15 minute(s). Form: Inhalable fraction TWA: 0.1 mg/m<sup>3</sup> 8 hour(s). Form: Inhalable fraction</p> <p><b>GKV_MAK (Austria, 6/2006).</b> STEL: 4 mg/m<sup>3</sup>, 4 times per shift, 15 minute(s). Form: Inhalable fraction TWA: 2 mg/m<sup>3</sup> 8 hour(s). Form: Inhalable fraction</p> <p><b>GKV_MAK (Austria, 6/2006).</b> STEL: 5 mg/m<sup>3</sup>, 1 times per shift, 30 minute(s). Form: Inhalable fraction TWA: 0.5 mg/m<sup>3</sup> 8 hour(s). Form: Inhalable fraction</p>
<p><b>Switzerland</b></p>	<p>Lead</p> <p>Antimony</p>	<p><b>EU OEL (Europe, 5/2006). Notes: Binding</b> 8 hours: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>SUVA (Switzerland, 2/2005). Notes: not temporary</b> TWA: 0.5 mg/m<sup>3</sup> 8 hour(s). Form: inhalable dust</p>
<p><b>Belgium</b></p>	<p>Lead</p> <p>Tin</p> <p>Antimony</p>	<p><b>Lijst Grenswaarden / Valeurs Limites (Belgium, 3/2006). Notes: As Pb</b> TWA: 0.15 mg/m<sup>3</sup>, (As Pb) 8 hour(s). Form: dust and fumes</p> <p><b>Lijst Grenswaarden / Valeurs Limites (Belgium, 3/2006). Skin</b> TWA: 2 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>Lijst Grenswaarden / Valeurs Limites (Belgium, 3/2006).</b> TWA: 0.5 mg/m<sup>3</sup> 8 hour(s).</p>
<p><b>Spain</b></p>	<p>Lead</p> <p>Tin</p> <p>Antimony</p>	<p><b>INSHT (Spain, 1/2006).</b> TWA: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>INSHT (Spain, 1/2006).</b> TWA: 2 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>INSHT (Spain, 1/2006).</b> TWA: 0.5 mg/m<sup>3</sup> 8 hour(s).</p>
<p><b>Turkey</b></p>	<p>Lead</p>	<p><b>EU OEL (Europe, 5/2006). Notes: Binding</b> 8 hours: 0.15 mg/m<sup>3</sup> 8 hour(s).</p>
<p><b>Czech Republic</b></p>	<p>Lead</p> <p>Antimony</p>	<p><b>178/2001 (Czech Republic, 6/2004).</b> STEL: 0.2 mg/m<sup>3</sup> 10 minute(s). TWA: 0.05 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>178/2001 (Czech Republic, 6/2004). Notes: as Sb</b> STEL: 1.5 mg/m<sup>3</sup>, (as Sb) 10 minute(s). TWA: 0.5 mg/m<sup>3</sup>, (as Sb) 8 hour(s).</p>

## MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

<b>Ireland</b>	<p>Lead <b>NAOSH (Ireland, 3/2002).</b> OELV-8hr: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p>Antimony <b>NAOSH (Ireland, 3/2002).</b> OELV-8hr: 0.5 mg/m<sup>3</sup> 8 hour(s).</p>
<b>Italy</b>	<p>Lead <b>Ministero della Salute (Italy, 3/2004).</b> TWA: 0.15 mg/m<sup>3</sup> 8 hour(s).</p>
<b>Estonia</b>	<p>Lead <b>Sotsiaalminister (Estonia, 9/2001).</b> TWA: 0.05 MG/M3 8 hour(s). Form: inhalable dust TWA: 0.1 MG/M3 8 hour(s). Form: total dust</p> <p>Antimony <b>Sotsiaalminister (Estonia, 9/2001).</b> TWA: 0.5 MG/M3 8 hour(s).</p>
<b>Lithuania</b>	<p>Lead <b>Del Lietuvos Higienos Normos (Lithuania, 12/2001).</b> TWA: 0.15 MG/M3 8 hour(s). Form: Inhalable fraction TWA: 0.07 MG/M3 8 hour(s). Form: Respirable fraction</p> <p>Bismuth <b>Del Lietuvos Higienos Normos (Lithuania, 12/2001).</b> TWA: 0.5 mg/m<sup>3</sup> 8 hour(s). Form: All forms</p> <p>Antimony <b>Del Lietuvos Higienos Normos (Lithuania, 12/2001).</b> TWA: 0.5 MG/M3 8 hour(s).</p>
<b>Slovakia</b>	<p>Lead <b>Nariadenie Vlády Slovenskej republiky (Slovakia, 5/2006).</b> TWA: 0.15 mg/m<sup>3</sup> 8 hour(s).</p> <p>Antimony <b>Nariadenie Vlády Slovenskej republiky (Slovakia, 5/2006).</b> CEIL: 1 mg/m<sup>3</sup> Form: total dust TWA: 0.5 mg/m<sup>3</sup> 8 hour(s). Form: total dust</p>
<b>Hungary</b>	<p>Lead <b>EüM-SzCsM (Hungary, 11/2002). Notes: as Pb</b> PEAK: 0.6 mg/m<sup>3</sup>, (as Pb) 15 minute(s). PEAK: 0.2 mg/m<sup>3</sup>, (as Pb) 15 minute(s). Form: Respirable TWA: 0.15 mg/m<sup>3</sup>, (as Pb) 8 hour(s). TWA: 0.05 mg/m<sup>3</sup>, (as Pb) 8 hour(s). Form: Respirable</p> <p>Antimony <b>EüM-SzCsM (Hungary, 11/2002). Notes: as Sb</b> PEAK: 2 mg/m<sup>3</sup>, (as Sb) 15 minute(s). TWA: 0.5 mg/m<sup>3</sup>, (as Sb) 8 hour(s).</p>
<b>Poland</b>	<p>Lead <b>Ministra Pracy I Polityki Społecznej (Poland, 10/2005).</b> <b>Notes: Calculated as Pb</b> TWA: 0.05 mg/m<sup>3</sup>, (Calculated as Pb) 8 hour(s).</p> <p>Tin <b>Ministra Pracy I Polityki Społecznej (Poland, 10/2005).</b> <b>Notes: Calculated as Sn</b> TWA: 2 mg/m<sup>3</sup>, (Calculated as Sn) 8 hour(s). Form: smokes and dusts</p> <p>Antimony <b>Ministra Pracy I Polityki Społecznej (Poland, 10/2005).</b> <b>Notes: Calculated as Sb</b> STEL: 1.5 mg/m<sup>3</sup>, (Calculated as Sb) 15 minute(s). TWA: 0.5 mg/m<sup>3</sup>, (Calculated as Sb) 8 hour(s).</p>

## MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

<b>Slovenia</b>	Lead	<b>Uradni list Republike Slovenije (Slovenia, 4/2005).</b> PEAK: 0.4 MG/M3, 4 times per shift, 15 minute(s). Form: Inhalable fraction TWA: 0.1 MG/M3 8 hour(s). Form: Inhalable fraction
	Antimony	<b>Uradni list Republike Slovenije (Slovenia, 4/2005).</b> PEAK: 2 MG/M3, 4 times per shift, 15 minute(s). Form: Inhalable fraction TWA: 0.5 MG/M3 8 hour(s). Form: Inhalable fraction
<b>Latvia</b>	Lead	<b>LV Nat. Standardisation and Meterological Centre (Latvia, 11/2004).</b> STEL: 0.01 MG/M3 15 minute(s). TWA: 0.005 MG/M3 8 hour(s).
	Antimony	<b>LV Nat. Standardisation and Meterological Centre (Latvia, 11/2004).</b> STEL: 0.5 MG/M3 15 minute(s). Form: Dust TWA: 0.2 MG/M3 8 hour(s). Form: Dust
<b>Greece</b>	Lead	<b>PD 90/1999 (Greece, 2/2003).</b> TWA: 0.15 MG/M3 8 hour(s).
	Tin	<b>PD 90/1999 (Greece, 2/2003).</b> TWA: 2 MG/M3 8 hour(s).
	Antimony	<b>PD 90/1999 (Greece, 2/2003).</b> TWA: 0.5 MG/M3 8 hour(s).
<b>Portugal</b>	Lead	<b>Instituto Português da Qualidade (Portugal, 7/2004).</b> TWA: 0.05 MG/M3 8 hour(s).
	Tin	<b>Instituto Português da Qualidade (Portugal, 7/2004).</b> TWA: 2 MG/M3 8 hour(s).
	Antimony	<b>Instituto Português da Qualidade (Portugal, 7/2004).</b> TWA: 0.5 MG/M3 8 hour(s).
<b>Exposure Controls</b>		
<b>Occupational exposure controls:</b>	No special ventilation requirements	
<b>Hygiene Measures:</b>	Wash thoroughly after handling	
<b>Respiratory Protection:</b>	Not applicable. Recommended: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator	
<b>Hand Protection:</b>	Use strong, cut-resistant gloves suitable for handling metals. <1 hours (breakthrough time): disposable Vinyl	
<b>Eye Protection:</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended: face shield EN 166 3 9-B	
<b>Skin Protection:</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: overalls	

# MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>General Information</b>	
<b>Appearance</b>	
<b>Physical state</b>	Solid
<b>Colour:</b>	Silvery
<b>Important health, safety and environmental information</b>	
<b>Melting Point:</b>	350°C (581°F)
<b>Solubility:</b>	Insoluble in the following materials: cold water and hot water

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	This product is stable. Under normal conditions of storage and use, hazardous polymerisation will not occur
<b>Conditions to Avoid:</b>	No specific data
<b>Materials to Avoid:</b>	No specific data
<b>Hazardous decomposition products:</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced

## 11. TOXICOLOGICAL INFORMATION

<b>Potential Acute Health Effects</b>	
<b>Skin Contact:</b>	No known significant effects or critical hazards
<b>Acute Toxicity</b>	
<b>Over-Exposure signs/symptoms</b>	
<b>Target Organs:</b>	Contains material which causes damage to the following organs: blood, kidneys, lungs gastrointestinal tract, cardiovascular system, upper respiratory tract, skin, central nervous system (CNS), eyes, lens or cornea

## 12. ECOLOGICAL INFORMATION

<b>Aquatic Ecotoxicity</b>				
Product Name	List Name	Name on List	Classification	Notes
<b>United Kingdom (UK) Lead</b>	UK Occupational Exposure Limits EH40 - WEL	Lead	Carc. Carc	
<b>Netherlands Lead</b>		Lood Metallisch	Repro. Fertility category 3	
<b>Germany Lead</b>	Germany TRGS905	Blei metal, bioverfügbar	RF3	
<b>France Lead</b>	France Occupational exposure Limits	Plomb Métallique	Carc. C1 Carc. C2, Carc. C3 Repro. R1 Repro. R2 Repro. R3	
<b>Antimony</b>	France Occupational Exposure Limits	Antimoine	Carc. C1 Carc. C2 Carc. C3	

## MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

<b>Aquatic Ecotoxicity</b>				
<b>Product/Ingredient name</b>	<b>Test</b>	<b>Result</b>	<b>Species</b>	<b>Exposure</b>
<b>Lead</b>	Mortality	Acute LC50 542 mg/L	Fish	96 hours
	Mortality	Acute LC50 471 mg/L	Fish	96 hours
	Mortality	Acute LC50 1.17 mg/L	Fish	96 hours
<b>Biodegradability</b>				
<b>Other adverse effects:</b>	No known significant effects or critical hazards			
<b>AOX:</b>	The product does not contain organically bound halogens which could lead to an AOX value in waste water.			

### 13. DISPOSAL CONSIDERATIONS

<b>Methods of disposal:</b>	The generation of waste should be avoided or minimised wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
<b>European Waste Catalogue (EWC):</b>	06 04 05* wastes containing other heavy metals
<b>Hazardous Waste:</b>	Yes

### 14. TRANSPORT INFORMATION

<b>International transport Regulations</b>						
<b>Regulatory Information</b>	<b>UN No</b>	<b>Proper Shipping Name</b>	<b>Classes</b>	<b>PG*</b>	<b>Label</b>	<b>Additional Information</b>
<b>ADR/RID Class</b>	<b>Not Regulated</b>	-	-	-		-
<b>IMDG Class</b>	<b>Not Regulated</b>	-	-	-		-
<b>IATA Class</b>	<b>Not Regulated</b>	-	-	-		-
<b>PG* - Packing Group</b>						

### 15. REGULATORY INFORMATION

<b>EU Regulations</b>	
Classification and labelling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.	
<b>Risk Phrases:</b>	This product is not classified according to EU legislation
<b>Product use:</b>	Industrial applications
<b>Other EU Regulations</b>	
<b>Additional Warning Phrases:</b>	Safety data sheet available for professional user on request
<b>France:</b>	
<b>Professional Disease or Diseases:</b>	Lead            RG 1 Antimony      RG 73
<b>Germany</b>	
<b>Hazard Class for Water:</b>	nwg Appendix No. 4
<b>Technical Instruction of Air Quality Control:</b>	TA-Luft Class 1 – Number 5.2.7.1.3: 70.1% TA-Luft Number 5.2.1: 29.9%
<b>Italy:</b>	
<b>Emission Control Directive:</b>	Not classified

# MATERIAL SAFETY DATA SHEET FOR BOSS LEADED SOLDER WIRE

## 16. OTHER INFORMATION

<b>Full text of R-phrases referred to in Sections 2 and 3 – Europe:</b>	R61 R62 R20/22 R33 R50/53 R51/53	May cause harm to unborn child Possible risk of impaired fertility Harmful by inhalation and if swallowed Danger of cumulative effects Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
<b>Full text of classifications referred to in Sections 2 and 3 – Europe:</b>	Repr. Cat. 1 Repr. Cat. 3 Xn N	Toxic to reproduction Category 1 Toxic to reproduction Category 3 Harmful Dangerous for the Environment
<b>References</b>  The Health and Safety At Work Act 1974, section 6 Control of Substances Hazardous to Health (CoSHH) Regulations 2002 and its amendments  Preparation contains solely TSCA and EINECS listed substances  This safety data sheet has been prepared in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 which implement EC Directives 1999/45/EC and 2001/58/EC and their amendments		
<b><u>DISCLAIMER</u></b>  <b>This information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.</b>		